





BC846PNV Plastic-Encapsulate Transistors

DUAL TRANSISTOR (NPN+PNP)

FEATURES

- Epitaxial Die Construction
- Two isolated NPN/PNP(BC846+BC856) Transistors in one package

MAKING: PJ



MAXIMUM RATINGS TR1 ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	80	V
V_{CEO}	Collector-Emitter Voltage	65	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current –Continuous	0.1	A
P_C	Collector Power Dissipation	200	mW
T_J	Junction Temperature	150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature	-55-150	$^{\circ}\text{C}$

SOT-563

CHARACTERISTICS of TR1 (NPN Transistor) ($T_a=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=10\mu\text{A}, I_E=0$	80			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=10\text{mA}, I_B=0$	65			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=1\mu\text{A}, I_C=0$	6			V
Collector cut-off current	I_{CBO}	$V_{CB}=30\text{V}, I_E=0$			15	nA
Emitter cut-off current	I_{EBO}	$V_{EB}=5\text{V}, I_C=0$			15	nA
DC current gain	h_{FE}	$V_{CE}=5\text{V}, I_C=2\text{mA}$	200		450	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=10\text{mA}, I_B=0.5\text{mA}$			0.25	V
	$V_{CE(sat)}$	$I_C=100\text{mA}, I_B=5\text{mA}$			0.6	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C=10\text{mA}, I_B=0.5\text{mA}$		0.7		V
	$V_{BE(sat)}$	$I_C=100\text{mA}, I_B=5\text{mA}$		0.9		V
Base-emitter voltage	$V_{BE(on)}$	$V_{CE}=5\text{V}, I_C=2\text{mA}$	0.58		0.7	V
	$V_{BE(on)}$	$V_{CE}=5\text{V}, I_C=10\text{mA}$			0.72	V
Collector output capacitance	C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$			6.0	pF
Transition frequency	f_T	$V_{CE}=5\text{V}, I_C=10\text{mA}, f=100\text{MHz}$	100			MHz
Noise figure	NF	$V_{CE}=5\text{V}, I_C=0.2\text{mA}, f=1\text{kHz}, R_g=2\text{K}\Omega, \Delta f=200\text{Hz}$			10	dB



MAXIMUM RATINGS TR2 ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	-80	V
V_{CEO}	Collector-Emitter Voltage	-65	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_{C}	Collector Current –Continuous	-0.1	A
P_{C}	Collector Power Dissipation	200	mW
T_{J}	Junction Temperature	150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature	-55-150	$^{\circ}\text{C}$









CHARACTERISTICS of TR2 (PNP Transistor) ($T_a=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(\text{BR})\text{CBO}}$	$I_{\text{C}}=-10\mu\text{A}, I_{\text{E}}=0$	-80			V
Collector-emitter breakdown voltage	$V_{(\text{BR})\text{CEO}}$	$I_{\text{C}}=-10\text{mA}, I_{\text{B}}=0$	-65			V
Emitter-base breakdown voltage	$V_{(\text{BR})\text{EBO}}$	$I_{\text{E}}=-1\mu\text{A}, I_{\text{C}}=0$	-5			V
Collector cut-off current	I_{CBO}	$V_{\text{CB}}=-30\text{V}, I_{\text{E}}=0$			-15	nA
Emitter cut-off current	I_{EBO}	$V_{\text{EB}}=-5\text{V}, I_{\text{C}}=0$			-15	nA
DC current gain	h_{FE1}	$V_{\text{CE}}=-5\text{V}, I_{\text{C}}=-2\text{mA}$	220		475	
Collector-emitter saturation voltage	$V_{\text{CE(sat)}}$	$I_{\text{C}}=-10\text{mA}, I_{\text{B}}=-0.5\text{mA}$			-0.3	V
	$V_{\text{CE(sat)}}$	$I_{\text{C}}=-100\text{mA}, I_{\text{B}}=-5\text{mA}$			-0.65	V
Base-emitter saturation voltage	$V_{\text{BE(sat)}}$	$I_{\text{C}}=-10\text{mA}, I_{\text{B}}=-0.5\text{mA}$		-0.7		V
	$V_{\text{BE(sat)}}$	$I_{\text{C}}=-100\text{mA}, I_{\text{B}}=-5\text{mA}$			-0.95	V
Base-emitter voltage	$V_{\text{BE(on)}}$	$V_{\text{CE}}=-5\text{V}, I_{\text{C}}=-2\text{mA}$	-0.6		-0.75	V
	$V_{\text{BE(on)}}$	$V_{\text{CE}}=-5\text{V}, I_{\text{C}}=-10\text{mA}$			-0.82	V
Collector output capacitance	C_{ob}	$V_{\text{CB}}=-10\text{V}, I_{\text{E}}=0, f=1\text{MHz}$			4.5	pF
Transition frequency	f_{T}	$V_{\text{CE}}=-5\text{V}, I_{\text{C}}=-10\text{mA}, f=100\text{MHz}$	100			MHz
Noise figure	NF	$V_{\text{CE}}=-5\text{V}, I_{\text{C}}=-0.2\text{mA},$ $f=1\text{kHz}, R_{\text{g}}=2\text{K}\Omega, \Delta f=200\text{Hz}$			10	dB



Typical Characteristics









BC846PNV/TR1






Typical Characteristics

BC846PNV/TR2






SOT-563 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.525	0.600	0.021	0.024
A1	0.000	0.050	0.000	0.002
e	0.450	0.550	0.018	0.022
c	0.090	0.160	0.004	0.006
D	1.500	1.700	0.059	0.067
b	0.170	0.270	0.007	0.011
E1	1.100	1.300	0.043	0.051
E	1.500	1.700	0.059	0.067
L	0.100	0.300	0.004	0.012
L1	0.200	0.400	0.008	0.016
θ	7 °REF.		7 °REF.	

SOT-563 Suggested Pad Layout




Note:

- 1.Controlling dimension:in millimeters.
- 2.General tolerance:±0.05mm.
- 3.The pad layout is for reference purposes only.



SOT-563 Embossed Carrier Tape



Packaging Description:

SOT-563 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter											
Pkg type	A	B	C	d	E	F	P0	P	P1	W	
SOT-563	1.78	1.78	0.69	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00	

SOT-563 Tape Leader and Trailer

